

# TRIMBLE PRO SERIES

## KEY FEATURES

### Trimble Floodlight satellite shadow reduction technology

More positions and increased accuracy in tough environments

### Work your way

Choose your configuration, data collector, and software

### Real-time decimeter accuracy

Confidence in the data you collect in the field

### Rugged design, built for the field

Works in the harsh physical environments you work

### Field-swappable battery

All day operation and the convenience of swap-and-go battery replacement

## TRIMBLE PRODUCTIVITY, YOUR WAY

With the flexibility to do it all, Trimble® Pro series receivers deliver unparalleled freedom of choice in professional GIS data collection. As the next generation of the Trimble GPS Pathfinder® family, the Trimble Pro series lets you configure a solution to match a wide range of work situations:

- Handheld or tablet data collector
- Real-time or postprocessed workflows
- Connectivity via Bluetooth®, serial, or USB to external devices
- In a backpack, on a pole, or mounted on a vehicle

With the Trimble Pro series receiver collect data your way, while maintaining the high-accuracy and position availability you need to stay productive.

## Dedicated to GIS data collection

Trimble Pro series receivers are built to withstand the rigors of long hours in tough outdoor conditions yet optimized for high-accuracy GIS data collection workflows. The integrated antenna reduces the complexity of the complete system for fast setup and swift data collection campaigns. Field workers can be up and running with minimal training saving time and money.



Trimble Pro series receivers improve GNSS productivity with Trimble Floodlight™ technology for improved satellite availability and Trimble H-Star™ technology for high-accuracy data logging. The Trimble Pro series can deliver down to decimeter accuracy—either postprocessed or in real time for the confidence the job is done right while still on site. Using Trimble TerraSync™ software or Trimble Positions™ Mobile extension in the field or other GIS-centric field workflows, Trimble Pro receivers are designed to deliver attribute-rich field data quickly and easily

## Stay out of the shadows with Trimble Floodlight

For maximum productivity in high-accuracy applications, Trimble Floodlight technology lets you take high-accuracy data collection into the toughest GNSS environments. Trees and buildings create “satellite shadows”, limiting the areas where you can reliably collect high-accuracy GNSS data. Using Floodlight technology, the Pro series keeps your teams productive without reducing accuracy. Work with fewer disruptions and ensure better data, faster data collection and higher field efficiency.



## Flexible to fit with the way you work

With your preferred configuration, choice of real-time or postprocessed workflows, decimeter or submeter accuracy-levels, and optional Floodlight technology—Trimble Pro series receivers enable you to work productively how and where you need to.



# TRIMBLE PRO SERIES

## PRODUCT MODELS

	Pro 6H	Pro 6T
Accuracy	Decimeter	Submeter
Floodlight	Yes	Optional

### GNSS

Receiver . . . . . Trimble Maxwell™ 6 GNSS chipset  
 Channels . . . . . 220 channels  
 Systems . . . . . GPS, GLONASS, WAAS/EGNOS/MSAS/GAGAN  
 Update rate . . . . . 1 Hz  
 Time to first fix . . . . . 45 s (typical)  
 NMEA-0183 support . . . . . Optional  
 Trimble Floodlight technology . . . . . Optional  
 RTCM support . . . . . RTCM2.x/RTCM3.x  
 CMR support . . . . . CMR/CMR+/CMRx

### Trimble Pro 6T receiver

GPS . . . . . L1C/A  
 GLONASS . . . . . L1C/A, L1P

### Trimble Pro 6H receiver

GPS . . . . . L1C/A, L2C, L2E  
 GLONASS . . . . . L1C/A, L1P, L2C/A, L2P

### GNSS ACCURACY<sup>1</sup>

#### Real-time DGNSS (Horizontal RMS)

Code . . . . . 7.5 cm + 1.0 ppm  
 SBAS2 (WAAS/EGNOS/MSAS) . . . . . Typically < 1 m

#### Real-time and postprocessed H-Star (Horizontal RMS) (Trimble Pro 6H configurations)

Horizontal . . . . . 10 cm + 1.0 ppm

#### Postprocessed DGNSS (Horizontal RMS)

Code . . . . . 5.0 cm + 1.0 ppm  
 Carrier (after 45 minutes) . . . . . 1 cm + 2.0 ppm

### TEMPERATURE (MIL-STD-810G)

Operation . . . . . -20 °C to +60 °C (-4 °F to +140 °F)  
 Storage . . . . . -30 °C to +70 °C (-22 °F to +158 °F)

1 Accuracy and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended GNSS data collection practices. Specified Centimeter accuracy can normally be achieved for baselines of 30 km or less. Specified H-Star accuracy can normally be achieved for baseline lengths of 100 km or less. Centimeter and H-Star accuracy is typically achieved within 2 minutes. Carrier postprocessed accuracy is limited to data collected within 10 km of the base station used for corrections.  
 2 SBAS (Satellite Based Augmentation System). Includes WAAS; available in North America only, EGNOS; available in Europe only and MSAS; available in Japan only.  
 3 Actual run time will vary with conditions and environment of use.  
 4 Bluetooth type approvals are country specific. Pro series receivers have Bluetooth approval in the U.S. and in most European countries. For further information please consult your local reseller.

© 2012-2014, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and GPS Pathfinder are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Floodlight, GPS Analyst, GPSCorrect, H-Star, Maxwell, Positions, Tempest, TerraSync, and Tornado are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022501-289D (03/14)

### ENVIRONMENTAL (MIL-STD-810G)

Drop shock . . . . . 1.2 m (4 ft) to plywood over concrete  
 Functional shock . . . . . Method 516.6 Procedure I  
 Accidental drop on pole . . . . . 2 m (6.56 ft)  
 Vibration . . . . . Method 514.5 Procedure I Category 24  
 Relative humidity . . . . . 95% non-condensing  
 Altitude rating . . . . . Method 500.5  
 Maximum storage altitude . . . . . 12,192 m (40,000 ft)  
 Maximum operational altitude . . . . . 9,000 m (29,520 ft)  
 Chemical exposure . . . . . Method 504.1 Procedure I  
 Salt Mist . . . . . Method 509.5

### INGRESS PROTECTION

Water/Dust . . . . . IP65

### SIZE AND WEIGHT

Height . . . . . 204 mm (8 in)  
 Diameter . . . . . 138 mm (5.4 in)  
 Weight (inc. battery) . . . . . 1040 g (2.3 lb)

### BATTERY

Type . . . . . Rechargeable, removable Li-Ion  
 Capacity . . . . . 11.1 V 2.5 AH  
 Charge time . . . . . 4 hours (typical)

### BATTERY RUN TIME<sup>3</sup>

Typical . . . . . > 12 hours

### CONNECTORS & INPUTS

- Mini USB connector
- External power connector
- DE-9 serial connector
- External antenna connector

### WIRELESS

Bluetooth<sup>4</sup> . . . . . Version 2.1 + EDR

### IN THE BOX

- Trimble Pro series receiver
- AC Power adaptor
- Serial cable
- Rechargeable battery pack
- USB data cable
- Documentation

### OPTIONAL ACCESSORIES

- Trimble Tornado™ external GNSS antenna (Pro 6H receiver)
- Trimble Tempest™ external GNSS antenna (Pro 6T receiver)
- 1.5 m & 5 m external antenna cable
- Backpack kit for external antenna
- Vehicle power supply

### SOFTWARE COMPATIBILITY

- Trimble TerraSync software
- Trimble GPS Pathfinder Office software
- Trimble Positions software suite
- Trimble GPSCorrect™ extension for Esri ArcPad software
- Trimble GPS Analyst™ extension for Esri ArcGIS for Desktop software
- Trimble GPS Controller software
- Custom applications built with Mobile GIS Developer Community software development kits (SDKs)
- Third party NMEA-based applications

Specifications subject to change without notice.



TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

### NORTH AMERICA

Trimble Navigation Limited  
 10368 Westmoor Dr  
 Westminster CO 80021  
 USA

### EUROPE

Trimble Germany GmbH  
 Am Prime Parc 11  
 65479 Raunheim  
 GERMANY

### ASIA-PACIFIC

Trimble Navigation  
 Singapore Pty Limited  
 80 Marine Parade Road  
 #22-06, Parkway Parade  
 Singapore 449269  
 SINGAPORE

